Centrifugal fans







DATA SHEET

MODEL: D-ARD-BC-7.5-1728/9000-900



DESCRIPTION	UNIT	VALUE		
Flow Rate	(CFM / LPS)	9000 / 4247		
ESP	(Pa)	900		
Working Temp.	(Deg.Cel)	50		
Motor Rating	(HP / kW)	10.0 / 7.5		
Pole		2 P		
Volt/Phase		400V /3 Ph		
Frequency	(Hz)	60		
Operating Speed	(Rpm)	1728		
Motor Make, Origin		PYTHON		
Blade		Backward Curved		
BHP (NTP)	(HP / kW)	10.03 / 7.52		
dB(A)	(dB)	85.73		
Drive		Direct Driven		
Protection		IP 55		
Insulation	Class	F		
Efficiency		IE3		
Vibration Amplitude (Normal)	(mil)	1.66		

Material Specs:

Casing & Blades (Thk)	3 mm.
Casing (MOC)	Mild Steel
Impellor (MOC)	Mild Steel
Coating	Powder Coated (RAL 7035)
Total Weight (Kgs)	220

Included Accessories:

Drain plug, Inspection door, Motor Cover.

Optional Accessories:

VFD, Volume control damper, Sound attenuator, Bird mesh, Motorized damper, Ex. Motors

Warranty:


Dumech warrants this equipment from material defect and workmanship for a period of one year from the delivery date or shipment date. Any parts proven to be defective in this span of time will be replaced at our cost.


Motors equipped with our units are warranted by the motor manufacturer for a period of one year. Replacement or Re-conditioning of motors shall be done based on availability of stock at our cost (with in the warranty period).

Application:

- 1. Ventilation System.
- 2. Fume extraction system.

Discharge Positions:







^{*}All Drawings are subjected to change without prior notice.

Overall fan dimensions:

A	E	В	W	L	D	N	M
350	50	620	1290	1275	570	438	770

Performance curve:







Excellent Warranty Terms. Ask Us about it



Ready? Talk to our Sales Rep Call: +966 53 804 0908





Tel: 04 3474929, Fax: 04 3474917, P.O. Box:49771, Dubai - UAE E-mail:dumech@eim.ae, Web :www.dumech.com



BRANCH

Al Sulay Industyrial Area, Riyadh, Saudi Arabia





COMPLIANCE